

GWZQ7.R25745 - DOOR HINGES CERTIFIED FOR CANADA

Door Hinges Certified for Canada

See General Information for Door Hinges Certified for Canada

SIMONSWERK GMBH

R25745

Bosfelder Weg 5

33378 Rheda Wiedenbruck, GERMANY

Full mortise, concealed door hinges, Models TECTUSTE 525 3D, TE 526 3D, TE 526 3D Energy, TE 527 3D, TE 527 3D Energy, TE 626 3D A8, TE 626 3D A8 Energy, and TE 528 3D intended for use on swinging type Classified steel-covered composite, hollow-metal doors and frames rated up to 3 h; fiberglass, wood and plastic-covered composite doors rated up to 1-1/2 h; and wood-core doors and frames rated 20 min with a maximum overall door opening of 1219 mm (4 ft.) wide by 2743 mm (9 ft.) high for single swing and 2438 mm (8 ft.) wide by 2743 mm (9 ft.) high for standard pairs.

Full mortise, door hinges, Models VARIANTVX7612 3D, VX7611 3D, VX7511 3D, VX7512 (frame section) with the Models VX7729/160, VX7729/160-4N, VX7749/160, VX7729/4-1/2"x 4" ER, VX7729/4-1/2"x4-1/2" ER, VX7729/160x4" ER, VX7729/160x4-1/2" ER, (door section) intended for use on swinging type fire doors and frames rated up to and including 3 hr with a maximum overall door opening of 1219 mm (4 ft.) wide by 3048 mm (10 ft.) high for single swing and 2438 mm (8 ft.) wide by 3048 mm (10 ft.) high for standard pairs. The Models VX7501 3D/VX7560, VX7531 3D/VX 7561, VX7571 (frame section) is intended for use on swinging type composite core wood fire doors and frames rated up to and including 1-1/2 h, with a maximum overall door opening of 1219 mm (4 ft.) wide by 3048 mm (10 ft.) high for single swing and 2438 mm (8 ft.) wide by 3048 mm (10 ft.) high for standard pairs, in conjunction with a door section component.

Full mortise, door hinges, Models VARIANTVN 2927/160ER COMPACT PLANUM (frame & door section), VN 2927/160 COMPACT (frame & door section), VN 2927/4-1/2 x 4 COMPACT (frame & door section), VN 2927/4-1/2 x 4-1/2 COMPACT (frame & door section) intended for use on steel, steel composite, wood or wood composite swinging type fire doors and frames rated up to and including 1-1/2 h with a maximum overall door opening of 4 ft. (1219 mm) wide by 9 ft. (2743 mm) high for single swing and 8 ft. (2438 mm) wide by 9 ft. (2743 mm) high for standard pairs.

Full mortise, concealed door hinges, Models TECTUSTE, TE 340 3D, TE 340 3D Energy, TE 540 3D, TE 540 3D Energy, TE 540 3D A8, TE 540 3D A8 Energy, TE 640 3D, TE 640 3D Energy, TE 640 3D A8, TE 640 3D A8 Energy steel shall be used on swinging type fire doors and frames rated twenty minutes with a maximum overall door leaf size of 4 ft x 8 ft for single swing and 8 ft by 8 ft for standard pairs.

Last Updated on 2019-11-27

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners.. [Learn More](#)

[> Cookie Settings](#)

Accept